

FIXING LEAKS AT THE SPOUT SWIVEL

Replacement of the two gacos (kind of 'O' Ring)



SWITCH-OFF THE WATER PUMP

SWITCH ON THE WATER PUMP



1 UNSCREW BY HAND THE HANDLE PIN

↑
SCREW BY HAND THE HANDLE PIN



2 PULL OUT THE HANDLE

↑
INSERT THE HANDLE



3 UNSCREW BY HAND THE CHROME CAP

↑
SCREW BY HAND THE CHROME CAP



4 UNSCREW THE BRASS NUT

↑
SCREW THE BRASS NUT



5 PULL OUT THE CARTRIDGE

↑
INSERT THE CARTRIDGE (CHECK THE POSITION OF THE 2 PINS)



6 UNSCREW BY HAND THE UPPER BODY

↑
SCREW BY HAND THE UPPER BODY
CHECK THE UPPER WHITE TEFLON GASKET AND, IF DAMAGED, REPLACE IT



7 PULL OUT THE CENTRAL BODY WITH THE SPOUT

↑
INSERT THE CENTRAL BODY WITH THE SPOUT



8 REPLACE THE TWO GACOS (KIND OF 'O' RING) KEEPING THE WIDERSIDE FACING EACH OTHER



↑
CHECK THE LOWER WHITE TEFLON GASKET AND, IF DAMAGED, REPLACE IT

